

De-Foam

Foam Suppressor



Applications:

Carpet extractor:

Do not spray directly on carpet or floor. For best results, before starting the water extraction procedure, use the vacuum hose to suction 28-85 ml (1-3 oz) of solution into the recovery tank. De-Foam can also be added directly into the recovery tank. Additional De-Foam may be added during the procedure as required.

Auto-scrubber/wet vacuum:

Spray inside the tank and/or directly into vacuum hose before starting pick-up.

Parts washing:

Add 28-85 ml (1-3 oz) to the solution reservoir.

Benefits:

- Prevents and controls unwanted foam in carpet extractors, auto-scrubbers, wet vacuums and while washing parts
- Maximizes the performance of your equipment
- Safe to use with any equipment that uses a cleaning solution

Codes:

- **Product Code:** 53156
- **UPC:** 0 56069 53156 6

Specifications:

Colour	White
DIN	No
Odour	Mild
pH	7.0 - 10.0
Viscosity	300 – 1,000 cPs
Solvent	No
Phosphates	No
WHMIS	Yes
ECOLOGO®	No
Food Safe	Yes
Kosher	Yes
Shelf Life	Up to 3 years after manufacturing

Dilution Rates:

Carpet Extractor

28 - 85 ml (1 - 3 oz)

Auto-scrubber, Wet Vacuum

Concentrated



Parts Washing

28 - 85 ml (1 - 3 oz)

Available Format:



5 L

Packaging:

Bottle: 6.1" x 6.1" x 12.6" (14.7 x 14.7 x 31 cm)
12.25 lbs (5.6 kg)

Box: 12.4" x 12.4" x 13"
49 lbs (22.2 kg)
4 per case

