

DESCRIPTION

- FOR COMMERCIAL APPLICATIONS IN DRY AREAS E.G.: RETAIL STORES, CAR DEALERS GROCERY STORES...
- HIGHLY ENERGIZED ZEDLAN SPONGE COMBINES SOFTNESS AND RESILIENCE FOR EXCEPTIONAL RELIEF
- MAINTAINS FLEXIBILITY AND ANTI-FATIGUE PROPERTIES EVEN IN LOW TEMPERATURES
- AVAILABLE IN STANDARD 3/8" (#440) AND SUPREME 1/2" (#445, 33% MORE COMFORT) THICKNESS
- ALSO AVAILABLE WITH ANTI-MICROBIAL ADDITIVE OR WITH GROUND CORD FOR ANTI-STATIC APPLICATIONS (ASK CUSTOMER SERVICE)

SURFACE

PATTERN: EMBOSSED PEDDLE PATTERN

MATERIAL: ZEDLAN VINYL FOAM

AVERAGE DUROMETER (SHORE 00)

50 PER ASTM D2240

ABRASION RESISTANCE (WHEEL (H38-2000 REV)

≤ .5 GRAM LOSS PER ASTM D4060

COMPRESSION

12% @ 7 PSI PER ASTM D1667

RESILIENCY

≥ 33% PER ASTM D2632

ELECTRICAL PROPERTIES

10⁹ OHMS (Ω) PER ASTM D257

AVERAGE DENSITY

22 LBS/FT³ PER ASTM D1667

FLAMMABILITY

D.O.C. FF 1-70 (MEETS THE FLAMMABILITY REQUIREMENTS)

COMFORT-KING

ERGONOMIC MATTING

AVERAGE THICKNESS AND WEIGHT

440: 3/8" 0,76 LB/FT²

445: 1/2" 0,90 LB/FT²

SIZES

MATS: 2' X 3', 3' X 5', 3' X 12'

ROLLS*: 2' X 60', 3' X 60', 4' X 60', 6' X 60'. (*NOT AVAILABLE WITH YELLOW BORDERS)

CUSTOM MATS: UP TO 6' X 60'

COLORS

ROYAL BLUE, STEEL GRAY, BLACK, BLACK WITH YELLOW BORDERS

ENVIRONMENT

DRY AREA

WARRANTY

TOTAL CONFIDENCE