



IPS GENERAL PURPOSE COLORS

Facestock: A coated face sheet, which provides excellent printing in handheld impact printers.

Basis Weight: 52#/ream (25x38)
Caliper: 4.0 mils
Tensile: 24# MD (min)
12.5# CD (min)
Tear: 40 g MD (min)
40 g CD (min)
Stiffness: 100 mg MD (min)

Adhesive: All Temperature acrylic adhesive with good initial tack to corrugated, glass, metal and plastics. Developed to minimize adhesive cold flow problems. And has excellent UV and plasticizer resistance.

Adhesive Weight: 12#/ream (24x36)
Adhesion: 1.2#/in
Minimum Application Temperature: -10°F
Service Temperature Range: -65°F to +200°F

Liner:
Basis Weight: 40#/ream (24x36)
Caliper: 2.5 mils
Tensile: 35# MD
15# CD
Tear: 45g MD
45g CD

FDA Compliance: Title 21, Section 175.105 of the Code of Federal Regulations (21 CFR 175.105). Compliance to this regulation permits the use of this adhesive in applications for which the adhesive either (1) is separated from the food by a functional barrier, which will prevent the migration of any of the adhesive components to the food, or (2) has incidental contact with food limited to the trace amount at the seams or the edges of the label.

