**B1200** BATTERY POWERED FRICTION WELD TOOL

UP TO: 3/4 in. x .050 PET STRAP or PP STRAP



## **1200** Ibs Tension

SPECIFICATIONS B600	
LxWxH	11.8" x 5.9" x 6.3"
WEIGHT	8.8 lbs.
BATTERY	14.8V-3.0 A/H LI-PO
MAX. TENSION	1200 lbs.
TENSION SPEED	7.9 in/sec
SEALING/JOINT STRENGTH	Friction / 80% of Breaking
RECOMMENDED STRAP SIZE/THICKNESS	5/8" - 3/4" polypropylene or polyester / .031"050"

**B600** BATTERY POWERED FRICTION WELD TOOL

UP TO: 5/8 in. x .030 PET STRAP or PP STRAP



## **600** Ibs Tension

SPECIFICATIONS	
LxWxH	11.8" x 5.9" x 6.3"
WEIGHT	8.8 lbs.
BATTERY	14.8V-2.0 A/H LI-PO
MAX. TENSION	600 lbs.
TENSION SPEED	10.4 in/sec
SEALING/JOINT STRENGTH	Friction / 80% of Breaking
RECOMMENDED STRAP SIZE/THICKNESS	1/2" - 5/8" polypropylene or polyester / .019"030"

## **B600 & 1200 SERIES ACCESSORIES**



BATTERY CHARGER	
PRODUCT CODE	
600CHG*	
POWER SUPPLY	
60 Hz 80W	
OUTPUT	
16.8V 5A	

<sup>\*</sup> Charges both B600 and B1200 Batteries



**Product Code: 190259** FOR TOOL COUNTERBALANCER SEE PAGE 15



BATTERIES		
PRODUCT CODE		
B600BAT	B1200BAT	
TYPE		
LITHIUM POLYMER	LITHIUM POLYMER	
OUTPUT		
14.8V 2.0AH	14.8V 3.2AH	

CHARGE TIME IS JUST 20 MINUTES & THE BATTERY PROVIDES FOR APPROXIMATELY 200 CYCLES & A LIFE OF UP TO 2,000 CHARGES.