# TECHNICAL SPEC. SHEET

Printed on: October 19 2023

# 5006.00.00 Container Magik clear 24 oz

## Typical application

- Take out item
- Soup
- Sauce
- Fruit salad
- Prepared salads
- · Nutritional supplements
- Confectionary
- Spreads



## Features & Benefits

- Easy to open and use
- Liquid tight
- · High definition photo quality IML decoration

Use

- · To open: Lift the lid
- To close: Press on the center of the lid to evacuate the air and close the snap









Material

Clear Polypropylene (BPA Free)

Product Code

5006.00.00

Technical Specifications

Capacity under lid Wall Thickness [mL] [in] 778 0,028

Approx Weight [g] 28,91

Overall Height [in] [mm] 5,00 127,00 Overall Diameter [in]

[mm] 4,45 113,03

### Decoration IML

- In-Mold-Labeling (IML): 4 color process (CMYK) and 4 additionnal PMS colors if required
- Container: Die line to be supplied
- Lid: Die line to be supplied

| Ordering Information |       |          |     |      |        |         |             |                     |       |        |                        |       |        |
|----------------------|-------|----------|-----|------|--------|---------|-------------|---------------------|-------|--------|------------------------|-------|--------|
| Code                 |       |          |     | Qty/ | Box/   | Weight/ | Weight/     | Box Dimensions [in] |       |        | Pallet Dimensions [in] |       |        |
| Product              | Color | Material | IML | box  | pallet | box[kg] | pallet [kg] | Length V            | Nidth | Height | Length                 | Width | Height |
| 5006 .               | XXX   | . XX .   | XXX | 500  | 24     | 14,5    | 346,92      | 22,5                | 13,75 | 20,25  | 48                     | 43    | 87     |

Contact your representative or customer service for exact ordering code

Packaged in cardboard boxes with inner bag

#### Top loading resistance

2,0 kg

4,4 lbs

at 73 F (23 C) for 30 days

Product temperature when filling containers and warehouse temperature will affect container performance. Elfe Plastik recommends performing necessary testing prior to full production.

#### Storing and distribution

No double pallet stacking. Shelving in a dry and tempered space is recommended.

For sale to manufacturers, distributors and end consumers. Storage period is 3 years.

#### Recommendations

- Handling conditions vary from customer to customer; therrefore, we recommend to validate your processes (filling, conveying, warehousing, etc.) with specific product testing.
- For optimal stacking stability and top load resistance, we recommend releasing the air from the container when putting on the lid.
- All containers to be packed in carboard box.
- Do not exceed pallets edges with containes.
- Stretch wrapping machine tension should be adjusted to container.
- Maximum filling temperature is at 212 F (100 C) Before closing temperature to be tested by the customer.
- Minimum temperature use is 4 °C.
- Can be used in microwave or washing machine.

# Chemical compatibility

Some chemicals can affect the integrity of the container. Any product requiring a Material Safety data Sheet (MSDS) has to be submitted to Elfe Plastik. If the buyer fails to adhere to this clause the related product guarantees will be void.

#### Certifications

Raw materials used are tested according to ASTM standards for polymers, approved for food contact and meet FDA (Food and Drug Administration USA) and CFIA (Canadian Food Inspection Agency) regulations.