

BubbleWrap® Paper Padded Mailer LP – Technical Information Sheet

Property	Requirements	Test Method
Inside Dimension	Width \pm 5 mm	ISO 4592
Outside Dimensions	Length \pm 10 mm Width \pm 5 mm	ISO 4592
Sizes Available	APAC: #0 - #7 US: #000 - #7	SEE Specs.
Print	Sharp, no smudges	SEE Specs.
Side Seam Strength	> 10 N/25 mm or fiber tear	ASTM D882 GB/T 12914
Self-Seal Strength (Flap)	> 10 N/25 mm at 180° pull or fiber tear	ASTM D882 GB/T 12914
Workmanship	Uniformly constructed, free from holes, tears, cuts, splits or other defects which might impair their usefulness	CID A-A-160E

- CID = Commercial Item Description A-A-160E
- SEE = Sealed Air Corporation
- 100% curbside recyclable
- FSC certified paper

NOTICE: While values shown are typical of this product, they should not be construed as specification limits. Sealed Air makes no warranties, expressed or implied, including without limitation, warranties of merchantability or fitness for a particular purpose, with respect to any product, information or recommendations referred to herein, and shall not be liable for any loss or damage, directly or indirectly, related to such product, information or recommendations or for consequential or incidental damages. User should test each application to determine suitability of the product for the intended use.