




POLYAIR

TECHNICAL PRODUCT SPECIFICATION

Revision No	1	Customer	General Specification
Issue Date:	23-Apr-2024	Description	1/2" DURABUBBLE LITE 4'X250" SLIT 24 P12
Manufactured	Toronto ON		
Part Number	VLL VLL48S24P12		

PHYSICAL PROPERTIES:

PROPERTY	RESULT	U o M
NOMINAL CELL HEIGHT	1/2"	inches
MATERIAL TYPE	LLDPE/LDPE blend	
DEFLATION	< 5	%
MINIMUM USAGE TEMPERATURE	-50 (°C)	-58 (°F)
MAXIMUM USAGE TEMPERATURE	80 (°C)	176 (°F)
MELTING POINT	137 (°C)	275 (°F)
RECYCLED CONTENT	up to 20	%



FINISHED PRODUCT SPECIFICATIONS:

	Min	Target	Max
Total Roll Width (inch)	48	48.25	48.5
Roll Length (feet)	250	255	260
Weight (lbs) (with Core)	11.79	13.36	14.99
Perforation (inch)	11.75	12.00	12.25
Slit @ (inch)	23.75	24	24.25

Slit, Length and Perforation General Tolerances / Specifications

Widths	Length	Perforations
As specified ± 1/4"	As specified -0, + 3%	As specified ± 5%

PACKAGING

Quantity	1	Roll /Bag	Slits-->	2
----------	---	-----------	----------	---

Durabubble is made from a blend of low density polyethylene and linear low density polyethylene. Store drop off recyclable. May not be recyclable in your area.



The technical information, suggested uses and applications presented are made without charge and are believed to be reliable; however, POLYAIR disclaims responsibility for results of use of this information. POLYAIR makes no warranties, either express or implied, concerning our materials, including any statements or suggestions as being inducements. All users should rely on their own test in determining suitability. This product data sheet is effective from 23-Apr-2024 and supersedes all previously published data.

IPG- POLYAIR (Divison of Intertape Polymer Group)

Quality Assurance Department
 330 HUMBERLINE DRIVE, TORONTO, ON M9W 1R5
 TEL: 416-679-6600; FAX: 416-679-6610