

Model 5AG-5 by



HIGH CAPACITY



Model 5AG-5

**GREATER
DOOR CLEARANCE...
WASHES TALLER WARES**

Double Duty Model designed to multiply your dishwashing capability. Features 20 1/2" door opening, air-gap fill, dual screening. Washes 74 racks per hour with two powerful 1 1/2 HP Pumps.


Wash Sheet Pans Horizontally with the optional Pan Rack



Model 5AG-S

TAKES CARE OF BIG JOBS IN NO TIME FLAT

- Cleans 74 racks per hour
- Water consumption is 1.6 gallons per rack
- Great Door Clearance at 20 1/2"
- Top Mount Controls with Auto Start
- Stainless Steel air gap
- Quick release spray arms
- Two Quick service 1 1/2 HP pumps
- Door safety switch - external prime switches
- Delime Switch located in the control panel



Model 5AG-S

FAMILY MODELS

	5AGS	5S	5AHS
RATED CAPACITY (racks/hour)	74	56	46
WASH TIME (in seconds)	45	60	75
RINSE TIME (in seconds)	30	45	60
DWELL (in seconds)	15	15	15
TOTAL CYCLE TIME (in seconds)	90	120	150

WATER TEMPERATURE 120 Deg. F/49 Deg. C MINIMUM
 WATER CONSUMPTION (NSF) 3.2 GALS. PER CYCLE(12.1 Liters)
 MOTOR (2) 1.5 H.P. 1.125 KW
 ELECTRICAL RATING (NEC) 115 VOLTS Single Phase

Connect to two Supply Sources Using 8-6 AWG Copper Wire. Circuit Protection: 20 AMP Circuit Breaker or Fuse with a 20 Amp Rating

OR
 Connect to Supply Sources Using 8-6 AWG Copper Wire suitable for at least 75 Deg. C(167 Deg. F.)
 Circuit Protection: 40 AMP Circuit Breaker or Fuse with a 40 AQMP Rating

RACK SIZE (2) 19.75" Square (50.2cm Square)
 DOOR CLEARANCE 20 1/2" x 21" (52cm x 53cm)
 WATER INLET 3/4" FPT
 DRAIN SIZE (Scrap Trap) 2" Pipe
 HEIGHT (Doors Open) 79.875" (202.9cm)
 HEIGHT (Doors Closed) 71.25" (180.9cm)
 WIDTH (Overall) 49" (124.5cm)
 WIDTH (Table to Table) 44" (111.8cm)
 DEPTH (Overall) 34" (86.4cm)
 SHIPPING WEIGHT 446 lbs. (202.3 kg)
 SHIPPING DIMENSIONS 60" L x 36" W x 78" H (152.4 cm x 91.4 cm x 198.1 cm)

Effective: 4/05

© 4/05

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov