




POLYAIR

TECHNICAL PRODUCT SPECIFICATION

| | | | |
|--------------|---------------------|-------------|--------------------------------------|
| Revision No | | Customer | General Specification |
| Issue Date: | 18-Jun-2024 | Description | 3/16" DURABUBBLE LITE 4'X750' |
| Manufactured | Toronto ON | SLIT24 | |
| Part Number | VLS VLS48S24 | | |

| <u>PROPERTY</u> | <u>RESULT</u> | <u>U o M</u> |
|--------------------------------|------------------|--------------|
| NOMINAL CELL HEIGHT | 3/16 | inches |
| MATERIAL TYPE | LLDPE/LDPE blend | |
| DEFLATION | < 5 | % |
| MINIMUM USAGE TEMPERATURE | -50 (°C) | -58 (°F) |
| MAXIMUM USAGE TEMPERATURE | 80 (°C) | 176 (°F) |
| MELTING POINT | 137 (°C) | 275 (°F) |
| RESISTANCE TO REDUCED PRESSURE | < 10 | % |
| RECYCLED CONTENT | up to 20 | % |

| FINISHED PRODUCT | | | |
|--------------------------|-------|--------------|-------|
| | Min | Target | Max |
| Total Roll Width (inch) | 47.75 | 48 | 48.25 |
| Roll Length (feet) | 750 | 750 | 772 |
| Weight (Incl. Core, lbs) | 26.57 | 29.60 | 32.65 |
| Slit (inch) | 23.75 | 24 | 24.25 |



| PACKAGING | | | |
|------------------|---|------------|---------|
| Quantity | 1 | Roll / Bag | 2 slits |

Durabubble is made from a blend of low density polyethylene and linear low density polyethylene. Store drop off recyclable. May not be recyclable in your area.



The technical information, suggested uses and applications presented are made without charge and are believed to be reliable; however, POLYAIR disclaims responsibility for results of use of this information. POLYAIR makes no warranties, either express or implied, concerning our materials, including any statements or suggestions as being inducements. All users should rely on their own test in determining suitability

This product data sheet is effective from 18-Jun-2024 and supersedes all previously published data.

POLYAIR (Division of Intertape Polymer Group)

Quality Assurance

330 HUMBERLINE DRIVE, TORONTO, ON M9W 1R5

TEL: 416-679-6600; FAX: 416-679-6610