

WEAR BOND™ COMFORT KING™

460

PRODUCT SPECIFICATIONS

DESCRIPTION

DENSE ABRASION-RESISTANT ZEDLAN TOP SURFACE IS WEAR-BONDED TO A HIGHLY ERGONOMIC ZEDLAN FOAM PROVIDING A SOFTER MAT WITH EXCELLENT RESILIENCE AND OUTSTANDING WEAR PROPERTIES. WEAR-BONDED PROCESS MOLECULARY BONDS LAYERS TOGETHER WITHOUT THE USE OF ADHESIVES

SURFACE

PEBBLE DESIGN (#460) ZEDLAN VINYL FOAM AVAILABLE
DECK PLATE DESIGN (#560) IN 2 DESIGN

BACKING

BLUE ZEDLAN VINYL FOAM FUSED TO THE ZEDLAN SURFACE TO CREATE AN UNMATCHED LEVEL OF DURABILITY WITHOUT ADHESIVE

AVERAGE DUROMETER (SHORE 00)

TOP - 70 BOTTOM - 40
TABER ABRASION (1000 CYCLES): ≤ .25% PER ASTM D-4060
RESILIOMETER: 33 PER ASTM D-2362
COMPRESSION: .18 @ 7 PSI PER ASTM D-1667
AVERAGE DENSITY: 18 LBS/FT³ ASTM D-1667

FLAMMABILITY

MEETS THE FLAMMABILITY REQUIREMENT OF D.O.C.-FF-1-70 (PILL TEST)

AVERAGE THICKNESS

9/16"

SIZES

MATS: 2' X 3', 3' X 5', 3' X 12'
ROLLS: 2' X 75', 3' X 75', 4' X 75'
CUSTOM MATS: UP TO 4' X 75'

WEAR BOND™ COMFORT KING™

460

PRODUCT SPECIFICATIONS

COLOR

GREY, BLACK, BLACK & YELLOW

AVERAGE WEIGHT

0,76 LB/FT²

FUNCTION

DRY AREAS

WARRANTY

TOTAL CONFIDENCE